



**CCMC**  
13102-R



### NORMATIVE INFORMATION

Postech products are approved by the Canadian Construction Materials Centre (CCMC 13102-R). They were tested on-site by an engineering firm recognized by the CCMC. The technical evaluation indicates that Postech products respect the requirements of the CCMC guidelines for augered steel piles. Their performance is equivalent or superior to prescribed NBC 2010 standards.

MANUFACTURER:  
Pieux Vistech - Postech Screw Piles  
10260, Bourque boulevard  
Sherbrooke QC J1N 0G2  
Tel. : 819.843.3003  
Toll free: 1.866.277.4389  
Fax. : 819.868.0793  
postech-foundations.com

### PRODUCT CHARACTERISTICS

#### Physical and Chemical properties

<b>STEEL GRADE</b>	Conform to CAN/CSA G40.21-350W and/or ASTM A500 grade C
<b>ARC WELDING</b>	Conform to CSA W59-18
<b>HOT DIP GALVANIZATION</b>	Conform to ASTM-A123M
<b>THERMAL INSULATION</b>	Unique polyurethane foam
<b>Standard characteristics</b>	
<b>TUBING DIAMETER</b>	140 mm (5 1/2 in)
<b>BLADE DIAMETER</b>	From 355 to 610 mm (14 to 24 in)
<b>TUBING LENGTH</b>	Standard of 2.1 m and 3 m (7 ft and 10 ft)
<b>TUBING THICKNESS</b>	6.5 mm (0.258)
<b>BLADE THICKNESS</b>	12.7 mm (1/2 in) for diameter from 355 to 610 mm (14 to 24 in)
<b>ADAPTER HEADS</b>	Various forms as needed according to the project specifications
<b>EXTENSIONS</b>	Available according to project specifications

### ALLOWABLE MECHANICAL RESISTANCE (SLS)

<b>MAXIMUM COMPRESSIVE AND TENSILE OF TUBING</b>	530 kN (119 150 lb) <sup>(1)</sup>
<b>BENDING MOMENT OF TUBING</b>	23.3 kN.m (17 185 lb.ft)
<b>INSTALLATION TORQUE - MAXIMUM APPLICABLE</b>	43 320 N.m (31 950 lb.ft)
<b>BEARING CAPACITY (ULS)</b>	
<b>COMPRESSIVE TORQUE CORRELATION FACTOR (<math>K_t</math>)</b>	13,7 m <sup>-1</sup> (4,2 ft <sup>-1</sup> ) <sup>(2)</sup>

ULS = Ultimate Limit State    SLS = Service

(1) The maximum support value is applicable to steel tube only. The resistance is conditional on the composition of the on-site soil (granular and / or cohesive) and that the pile must be supported laterally. In all cases, the mechanical capacity of the steel tube must be certified by an authorized engineer. (Not applicable in the presence of liquefiable or loose soils, water, air, peat bogs, etc.)

(2) The  $K_t$  factor supplied by Postech is only applicable to determine plies compressive bearing capacity in, screwed into granular (cohesionless) soils. When the piles are used in tension, or in a cohesive soil, please contact Postech to determine its bearing capacity.

## SCREW PILES BEARING CAPACITY

$$Q_t = K_t \times T$$

- $Q_t$  = Ultimate bearing capacity.
- $K_t$  = Torque correlation factor.
- T = Average torque measured on the last 0,3 m (1 ft.) installation, in N.m or lb.ft.

To obtain the service bearing capacity (SLS), the value of  $Q_t$  must be divided by 2 (SF=2).

### LATERAL LOADS

ALLOWABLE LOADS (SLS) DEPENDING ON SOIL DENSITIES

SOIL DENSITIES (kN / m <sup>3</sup> )	P512 ALLOWABLE LATERAL LOADS (3)	
	(kN)	(Lb)
16	17.5	3 935
18	19.8	4 455
20	22.0	4 950
22	24.1	5 420

SLS = Service Limit State

(3) Lateral loads are applicable at the pile head, less than 0.3 m (1 ft) above ground, and the pile must be supported laterally by the ground. However, lateral loads do not apply in the presence of liquefiable or loose soils, water, air and peatlands. The lateral capacity of a pile must always be certified by an engineer licensed to practice under the appropriate provincial or territorial legislation. The safety factor for the lateral loads is equal or superior to 2.0.

Technical note :

- If there are any boulders (> 200 mm in diameter) in the granular matrix, the above mentioned capacities will be overstated. In this case, capacities must be established with on-site using a confirmatory test.

### DESIGN INFORMATION

In all cases, please refer to the CCMC 13102-R Assessment Report. All applicable loads must be validated by an engineer licensed to practice under the appropriate provincial or territorial legislation.


#### BEARING CAPACITY

Postech products are designed to bear compressive and tension loads through the blade at the bottom of the shaft. The design of the shaft and the size of the blade depend on the load and on the bearing capacity of the soil. The monitoring of the applied torque on-site allows for the confirmation of the ultimate and allowable bearing capacities (ULS and SLS) of the soil. All capacities listed on this data sheet must be applied at the pile head less than 0.3 m (1 ft) above ground, considering that pile is laterally supported until at grade.

#### THERMAL INSULATION

Postech products are insulated by a process of injecting polyurethane foam in the piles shaft. The revolutionary insulation system ensures that the inside of the pile is maintained at a temperature

### SCREW PILE ADVANTAGES

- Product and installation is supplied, you only need to mark the spot!
- Can be installed in all climates, weather or ground conditions;
- No excavation usually required, minimal impact to your property;
- No waiting time, you can build as soon as the installation is ready;
- Reusable and recyclable, environmentally friendly; 
- Can be installed under an existing structure;
- The most reliable & economical solution available.

**CCMC**  
13102-R



### NORMATIVE INFORMATION

Postech products are approved by the Canadian Construction Materials Centre (CCMC 13102-R). They were tested on-site by an engineering firm recognized by the CCMC. The technical evaluation indicates that Postech products respect the requirements of the CCMC guidelines for augered steel piles. Their performance is equivalent or superior to prescribed NBC 2010 standards.

#### MANUFACTURER:

Pieux Vistech - Postech Screw Piles  
10260, Bourque boulevard  
Sherbrooke QC J1N 0G2  
Tel. : 819.843.3003  
Toll free: 1.866.277.4389  
Fax. : 819.868.0793  
postech-foundations.com